

Specification - S Range




S Model Range	520 S				580 S				540 SC			600 SC	
	I	ILP	IE	IEP	I	ILP	IE	IEP	IC	ILPC	IEPC	ILPC	IEPC
Reach	5.25m	5.25m	5.25m	5.25m	5.85m	5.85m	5.85m	5.85m	5.45m	5.45m	5.45m	6.05m	6.05m
Cutting Width	1.2m	1.2m	1.2m	1.2m	1.2m								
Minimum Tractor Power	65hp	65hp	65hp	65hp	70hp	70hp	70hp	70hp	75hp	75hp	75hp	80hp	80hp
Left or Right Cut	0	0	0	0	0	0	0	0	0	0	0	0	0
Parallel Arm Geometry	S	S	S	S	S	S	S	S	S	S	S	S	S
Powerslew & Hydraulic Breakaway	S	S	S	S	S	S	S	S	S	S	S	S	S
Sprung Top Link	S	S	S	S	S	S	S	S	S	S	S	S	S
Flail Cutting Reversible by Remote Control	S	S	S	S	S	S	S	S	S	S	S	S	S
Fully Independent Hydraulics													
Cable Control	S				S				S				
Low Pressure Hydraulic Joystick Control		S				S				S			S
Electric Control			S				S						
Digital Proportional Joystick Control				S				S			S		S
Floatation													
Head Floatation	S	S	S	S	S	S	S	S	S	S	S	S	S
Boom Floatation Accumulator	0	0	0		0	0	0		0	0		0	
Boom Floatation Potentiometer				S				S			S		S
Options													
Cranked Variable Forward Boom (0.92m)									S	S	S	S	S
1.5m Head	0	0	0	0									
Rear Lights	0	0	0	0	0	0	0	0	0	0	0	0	0
Subframe Axle Mounting Kit	0	0	0	0	0	0	0	0	0	0	0	0	0
High Power 68 hp	0	0	0	0	0	0	0	0	0	0	0	0	0

0 = Optional
S = Standard

Cutting Dimensions

Model	Side Reach		Vertical Reach		Downward Reach
	Head Horizontal	Head Vertical	Head Vertical	Head Horizontal	
	A	B	C	D	E
520 S	5.25m	4.8m	6.4m	5.5m	3.4m
580 S	5.85m	5.4m	7.0m	6.1m	4.0m
540 SC	5.45m	4.8m	6.6m	5.5m	3.6m
600 SC	6.05m	5.85m	7.05m	6.05m	4.1m



Twose of Tiverton Ltd
6 Chinon Court, Lower Moor Way
Tiverton, Devon EX16 6SS, England
Tel: 01884 253691
Fax: 01884 255189
Email: sales@twose.com
www.twose.com

An Alamo Group Company



Designed to perform - built to last

The policy of Twose is one of continuing development and we reserve the right to change, without notice, prices, weights, measurements and specification of all machines detailed or illustrated in this leaflet, without incurring any obligation to provide modifications on machines previously delivered. Orders are accepted subject to our standard conditions of sale.



S Range Hedge trimmers

520 S - 5.25m reach
580 S - 5.85m reach

Variable Forward Reach
540 SC - 5.45m reach
600 SC - 6.05m reach





Twose 5 Range 520S and 580S

520S - 5.2m reach
580S - 5.8m reach

- Choice of Controls
- Super Slim Tank - reduced overhung weight - more stable - better oil cooling
- 95° Power Slew
- Cutter head 250mm further forward for better vision
- 245° smooth, constant head angling
- Parallel boom geometry
- Pumps and valves protected behind bumper bar
- All pipes inside boom elements
- Three point hitch and stabiliser



540SC and 600SC Variable forward reach cranked booms

**540SC - 4.6m reach fully cranked
extending to 5.4m**
**600SC - 5.2m reach fully cranked
extending to 6.0m**

- Hydraulic cranked outer boom
- Amount of forward crank is infinitely variable to suit driver and type of tractor
- Cutter head fully cranked 0.8m forward
- Driver always looking forward
- Suitable for subframe mounting

Better cutter head visibility
Better visibility of material to be cut
Better tractor mounting
Better operator comfort



Double Skin Cutter Head

Developed and built to meet the demands of prolonged use, the Double Skin Cutter Head offers many innovative features and practical advantages over traditional cutting heads.

- 1.2m (48") Double skin cutter head
- Double Skin top Cover gives torsional rigidity and improved wear resistance.
- Drive line contained within the width of skid
 - Simple belt adjustment
- Quick fit heavy duty rotor takes 5 types of flail
 - Heavy braced end panels
 - Adjustable heavy duty roller
- Skid wrapped well around panel for greater protection
 - Nose guard with barbed wire trap & heavy duty curtain
 - Choice of flails



Cable Control



Low Pressure Hydraulic Proportional Joystick Control




Electronic Switch Control



Electronic Joystick Control with Proportional Valves




Heavy Duty Reversible Lump Flail for hedging and occasional mowing. This flail is fitted as standard unless otherwise specified.



Heavy Duty Grass and Hedging Flail. Cuts in one direction only.



Back to Back Reversible Flails for grass cutting.



Cast Boot Flail and Shackle for mowing or hedging. Cuts in one direction only.



Back to Back Reversible Flails and Shackle for grass cutting.