



Multi-Farmer

	Total empty weight(with forks)	Rated max load	max lift height	max forward reach	lift height at full capacity	Reach at full capacity	capacity at full lift height	capacity at full forward reach	low emission euro 2 engine	power at 2400 rpm	Double Gear hydraulics pump	Pump capacity	BSS(Boom suspension)	Front and rear differential locks	Three double acting rear services	Hydraulic towing pick up hitch	hydraulic trailer braking	Rigid axle	Air conditioning	draw bar pull (on dynamoter)	Mechanical rear PTO	optional front PTO	3 point linkage lifting capacity
30.6 CLASSIC	6550kg	3000kg	6m	3.15m	6m	1.3m	3000kg	1500kg	4 cyl deutz/Turbo/Aftercooled	85kw/115hp	yes	107Lpm/210bar	-	yes	yes	-	-	yes	-	6000kg	540/1000 rpm	1000 rpm	4300kg
30.6 CLASSIC X	6550kg	3000kg	6m	3.15m	6m	1.3m	3000kg	1500kg	4 cyl deutz/Turbo/Aftercooled	85kw/115hp	yes	107Lpm/210bar	-	yes	yes	yes	yes	yes	-	6000kg	540/1000 rpm	1000 rpm	4300kg
30.6 TOP	6550kg	3000kg	6m	3.15m	6m	1.3m	3000kg	1500kg	4 cyl deutz/Turbo/Aftercooled	85kw/115hp	yes	107Lpm/210bar	yes	yes	yes	-	-	yes	yes	6000kg	540/1000 rpm	1000 rpm	4300kg
30.6 TOP X	6550kg	3000kg	6m	3.15m	6m	1.3m	3000kg	1500kg	4 cyl deutz/Turbo/Aftercooled	85kw/115hp	yes	107Lpm/210bar	yes	yes	yes	yes	yes	yes	yes	6000kg	540/1000 rpm	1000 rpm	4300kg
30.9 CLASSIC	6650kg	3000kg	8.55m	5.6	7.5m	1.7m	2500kg	600kg	4 cyl deutz/Turbo/Aftercooled	85kw/115hp	yes	107Lpm/210bar	-	yes	yes	-	-	yes	-	6000kg	540/1000 rpm	1000 rpm	4300kg
30.9 CLASSIC X	6650kg	3000kg	8.55m	5.6	7.5m	1.7m	2500kg	600kg	4 cyl deutz/Turbo/Aftercooled	85kw/115hp	yes	107Lpm/210bar	-	yes	yes	yes	yes	yes	-	6000kg	540/1000 rpm	1000 rpm	4300kg
30.9 TOP	6650kg	3000kg	8.55m	5.6	7.5m	1.7m	2500kg	600kg	4 cyl deutz/Turbo/Aftercooled	85kw/115hp	yes	107Lpm/210bar	yes	yes	yes	-	-	yes	yes	6000kg	540/1000 rpm	1000 rpm	4300kg
30.9 TOP X	6650kg	3000kg	8.55m	5.6	7.5m	1.7m	2500kg	600kg	4 cyl deutz/Turbo/Aftercooled	85kw/115hp	yes	107Lpm/210bar	yes	yes	yes	yes	yes	yes	yes	6000kg	540/1000 rpm	1000 rpm	4300kg
McM	Total empty weight(with forks)	Rated max load	max lift height	max forward reach	lift height at full capacity	Reach at full capacity	capacity at full lift height	capacity at full forward reach	low emission euro 2 engine	power at 2400 rpm	Double Gear hydraulics pump	Pump capacity	BSS(Boom suspension)	Front and rear differential locks	Three double acting rear services	Hydraulic towing pick up hitch	hydraulic trailer braking	Rigid axle	Air conditioning	draw bar pull (on dynamoter)	Mechanical rear PTO	optional front PTO	3 point linkage lifting capacity